

## Constant radius rail and slider system

CKR01 - 85° - 600 - 890 - 2 - CCT08 - NIC - R

Rail type	
Angle	
Radius	
Rails extended length	
Number of sliders	
Slider type	
Expanded surface protection (if other than standard)	
Right or left version	

## Variable radius rail and slider system

CVR01 - 39° - 200 - 23° - 400 - 297 - 2 - CCT08 - NIC - R

Rail type	
Angle	
Radius	
Angle	
Radius	
Rails extended length	
Number of sliders	
Slider type	
Expanded surface protection (if other than standard)	
Right or left version	

Note: Data for angles and respective radii are in sequential order.

Note: Information for right and left side installation and for expanded surface protection is only necessary if required. Rail lengths and radii always are indicated with four digits, angles always with three digits and a zero as prefix. Exact specifications (layout, angle, radius, hole pattern, etc.) must be represented in a drawing.

# Slider

CCT08 - NIC

Slider type

Expanded surface protection (if other than standard)

# Constant radius rails

CKR01 - 120° - 600 - 1152 - NIC - R

Rail type

Angle

Radius

Rails extended length

Expanded surface protection (if other than standard)

Right or left version

# Variable radius rails

CVR01 - 39° - 200 - 23° - 400 - 297 - NIC - R

Rail type

Angle

Radius

Angle

Radius

Rails extended length

Expanded surface protection (if other than standard)

Right or left version

Note: Data for angles and respective radii are in sequential order.

Note: Information for right and left side installation and for expanded surface protection is only necessary if required. Rail lengths and radii always are indicated with four digits, angles always with three digits and a zero as prefix. Exact specifications (layout, angle, radius, hole pattern, etc.) must be represented in a drawing.